

Type:	VLC __ (__=50,100,250,500,1000,1500)
eDMX	≤ __*512 channels
Total	≤ __*512 channels

Ethernet / Management

RJ45 socket, (10/100/1000 Base-TX)

- System integration
- Pharos Cloud
- Scale with Pharos devices
- Commissioning

RS232

DB9 connector

- System integration

Audio output


Left + Right cinch connector
SPDIF cinch connector

- To audio system

Mains input

IEC connector. UK, EU and US cable included

- From mains power installation
- 100-240V AC 50-60Hz 0.4-0.2A
- 40W typical, 100W maximum



Ethernet / Data

RJ45 socket (10/100/1000 Base-TX)

- eDMX output to lighting

USB

For service use only

DVI-D Input

DVI-I connector, only DVI-D supported

- For live video input

DVI-I Output

(future development)

- Consult the **Installation Guide** for technical details
- See **General Notes.pdf** for information on cabling types
- Contact your supplier, visit our website or mail support with any other questions



pharoscontrols.com

Reference:
0005

Size:
A4

Page:
1 of 1

Name:
VLC interfaces

Date:	Rev:	Notes:
27/09/2016	V 1.0	Setup
17/09/2018	V 1.1	Minor adjustments
21/01/2019	V 1.2	Minor adjustments
27/05/2021	V 1.3	Minor adjustments